



The AGCO® Allis 9735 and 9745 are the ones you'll want.

- New AGCO® Allis engine
- Transmission options
- 2WD or AWD
- Better cab view
- More operator view
- Armrest control console
- Tighter AWD steering angle
- Electronic 3-point hitch
- High performance hydraulics
- Easy engine maintenance

Think of all the great new ideas you'd like to see in a row crop tractor, and you've got the 125 PTO hp AGCO® Allis 9735 and 145 PTO hp 9745. They're powered by new AGCO Allis 600 Series liquid cooled diesels. And when you combine the clean, quiet, efficient performance of these 6 cylinder turbocharged engines with the new styling, comfort and performance features of the 9735 and 9745, you can see why it's a better business decision to get one.

GREAT NEW IDEAS ▶ BETTER BUSINESS
GET ONE
▶ AGCO



Get the facts and figures, and you'll just have to get one.



Start at one end of the streamlined new, AGCO® Allis 9735 and 9745, and work your way to the other. By the time you're finished, you'll realize just how innovation and dedication have gone into creating

a tractor that's all new from the ground up and the inside out. And once you drive one, the only thing left to do after that is get one.

New Style.
Low-profile hood for good looks and an even better view.

New Transmission Choices.
Standard 4-speed or optional 18-speed Powershift transmission.

Wet multi-disc clutch increases durability by cushioning torque loading surface while dissipating heat.

New View.
Cab designed for clear all-around visibility.

New Comfort.
Spacious interior and convenient controls for easier operation.

New Engine.
AGCO® Allis 600 Series turbocharged liquid cooled diesel.

New Control.
Improved hydraulic system for efficient versatility.

New Control.
3-point hitch with electronic controls.



AGCO Allis Model	9735	9745
Engine	AGCO® Allis Model 66.6T	AGCO® Allis Model 66.6TW
PTO HP (kW)	125 (93.2)	145 (108.1)
Rated Speed	2200 RPM	2200 RPM
Type	Liquid Cooled Diesel	Liquid Cooled Diesel
Aspiration	Turbocharged	Turbocharged & Intercooled
Displacement (cu in/liter)	402 (6.6)	402 (6.6)
Bore (in/mm)	4.25 (108)	4.25 (108)
Stroke (in/mm)	4.72 (120)	4.72 (120)
# Cylinders	6	6
Compression Ratio	16.5:1	16.5:1
Fuel Tank Capacity		
U.S. gal (L)	100 (378)	100 (378)
Clutch Type	Wet Multi Disc, Oil Cooled	Wet Multi Disc, Oil Cooled
Transmission		
Standard	4-Speed Powershift	4-Speed Powershift
Optional	18-Speed Powershift	18-Speed Powershift
Rear Axle Diameter in (mm)	3.75 (95)	3.75 (95)
Standard Axle Length in (mm)	98 (2489)	98 (2489)
Optional Axle Length in (mm)	118 (2997)	118 (2997)

AGCO Allis Model	9735	9745
Brake Type	Multi Disc, Oil Immersed	Multi Disc, Oil Immersed
Independent PTO	540/1000 rpm Standard	540/1000 rpm Standard
Economy 540/1000 PTO		
Hydraulic System		
Type	Closed Center	Closed Center
Max. Pressure psi (bar)	2900 (190)	2900 (190)
Max. Output gpm (lpm)	27.0 (114)	27.0 (114)
3-Point Hitch Category	II	II
3-Point Hitch Control	Electronic	Electronic
SAE 3-Point Hitch		
Lift Capacity @ 24" lbs (kg)	10400 (4717)	10400 (4717)
3-Point Hitch Stabilizers	Sway Block Telescope	Sway Block Telescope
Lower Draft Arm Link Ends		
Dimensions		
Minimum Width in (mm)	98 (2489)	98 (2489)
Height Top of Cab in (mm)	120 (3048)	120 (3048)
Length in (mm)	202 (5130)	202 (5130)
Wheelbase in (mm)	117.5 (2985)	117.5 (2985)
Approximate Shipping Weight		
2WD Cab lbs (kg)	15000 (6818)	15100 (6863)
AWD Cab lbs (kg)	16000 (7272)	16100 (7318)