

ISEKI

TRACTOR 4WD

SX 55



TRACTOR SX 55

Specifications

Tractor models		SX55 (4WD)	
Items		STD	L-type
Dimensions (mm)			
Overall length (from front to 3-p hitch end)		3,600	
Overall height (top of muff. cap)		1,885	
Wheel base		2,160	
Wheel tread	Front	1,420	
	Rear	1,320 - 1,770	
Minimum ground clearance		315	
Turning radius	w/brake	3.0	
	w/o brake	3.9	
Weight (kg)		2,445	2,455
Engine			
Model		4JB1	
Type		Water cooled, 4-cycle diesel	
Number of cylinders		4	
Output (DIN HP/rpm)		50/2,200(SAE55/2,200)	
Displacement (cc)		2,771	
Bore x Stroke (mm)		93 x 102	
Combustion chamber type		Direct injection	
Lubrication system		Forced-circulation	
Cooling system		Water cooled forced circulation	
Air-cleaner		Dry element with cyclone pre-cleaner/screen	
Fuel		Diesel	
Fuel tank capacity (ℓ)		60	
Starting method		Electric starter with glow plug	
Battery		12V - 110AH	
Chassis			
Clutch	Main clutch	13" dry single disc	
	PTO clutch (Independent)	Wet, multi-disc, hydraulic	
Transmission		Synchromesh	
Brakes		Wet, multi-disc (also serving as parking brakes)	
Steering system		Integral type power assisted	
Number of speed		12-forward	24-forward
		4-reverse	8-reverse (with creep shift)
Traveling speed (km/hr.)	Forward	2.1 ~ 30.3	0.36 ~ 30.3
	Reverse	4.8 ~ 10.7	0.85 ~ 10.7
Tire size	Front	8.3 - 20	
	Rear	14.9 - 28	
Implement lift			
Lifting capacity (kg)		2,400kg	
Pump capacity (ℓ/min.)		35	
Mounting method		Hydraulic 3-point linkage	
Towing method		Swing drawbar	
3-point hitch category		II	
Function		Position, draft and mix control	
PTO shaft		6-spline	
Speed (PTO)		540/1727	
	(rpm/Engine rpm)	1000/2000	

* Specifications are subject to change without notice.



STANDARD EQUIPMENT

ENGINE

Muffler with the cap, Fuel tank (60 liters), Cyclone air cleaner with pre-cleaner

CHASSIS

4 poles ROPS and roof, Two headlights, Turn signal lights, Two turn signal lights, Two tail lights, Two stop lights, Work lamp, Main clutch cut-off arm, Two warning hazard lights, Front differential lock device, Rear differential lock device, Sliding adjustable suspension seat, Engine shut off lever, Hydraulic control lever with position and draft, Handle tilt angle lock pedal, Steering wheel, Two rear mirrors, Hydraulic slow return knob, Battery, Safety starting device, Rear fenders, Two-speed rear PTO shaft and its guard, 3 point linkage (Cat. II), Swinging draw bar, Tool box and Tools

OPERATION CONTROL

Power steering device, Main speed shift lever, Sub shift lever, Creep shift lever (L type only), PTO speed shift lever, Hand throttle & accelerate pedal, Independent PTO lever, Hydraulic power take off lever, Brake pedals, Clutch pedals, Parking brake lever, 4 wheel drive shift lever, Power steering device

INSTRUMENT PANEL

Thermometer, Fuel meter, Engine speed/ tachometer, Hour meter, Monitor lights (Beam, F. diff. lock, R. diff. lock, glow, PTO, Engine oil, Charge, Parking, Air filter), Turn signal pilot lights, Main key switch, Headlights switch, Horn button, Turn signal switch, Warning hazard light switch, Fuse box

OPTIONAL EQUIPMENT

Sub fuel tank (30 liters), Linkage draw bar, Balance weight, Rear wheel weight

POWER FARMING WHOLESALE LTD.

P.O. Box 6, Morrinsville, New Zealand
Phone: (0819) 7177 Telex: POWFARM NZ 21590

MABER ISEKI PTY. LTD.

1632 Hume Hwy, Campbellfield 3061, Australia
Phone: (03) 359-2166 Telex: AA38963

ISEKI & CO., LTD.
Tokyo, Japan

A-1321-61 851110 Printed in Japan