

MITSUBISHI

MT372D MT372



New Multi-Purpose 15 hp Diesel Packaged for Peak Performance Under All Types of Work Conditions

Here's the mightiest of the compacts, a small Diesel that's loaded with big-tractor features . . . ideal for practically any job you throw its way.

- Choice of 2- or 4-wheel drive
- 2-cylinder, water-cooled engine
- Six forward speeds—two reverse
- Three-step PTO—565, 832 and 1,364 rpm
- Category 0 or I · 3-point hitch
- Most modern tractor in its class

MITSUBISHI MT372D MT372



FEATURES

Economy

The MT372D, MT372's functional 15 hp Diesel engine means not only low fuel consumption, but also low maintenance costs. In fact, most standard periodic maintenance can be done on-site eliminating costly and inconvenient down time. Plus, the tractor is so easy to use and is so versatile, a greater variety of jobs can be done and more members of your family can do them.

Versatility

The tractor's three-step PTO, category O or I 3-point linkage, eight-speed transmission and live hydraulic system allow you to match a wide range of implements to a wide range of applications all year round. The tractor's high ground clearance, superb traction and high-power output are ideal for row crop work. Equipped with estate tires and a mower, the tractor can care for any lawn, quickly and efficiently.

Comfort

The driver work station has been designed with easy-to-reach controls and a contoured seat for operator comfort and the reduction of operator fatigue.

Practicality

The tractor offers large-tractor capabilities in a functional, compact size. Available in both 2-wheel and 4-wheel drive, with either agricultural or estate tires, and capable of handling a wide range of rear, mid and front mounted implements, the tractor is the practical choice for most tractor needs.

SPECIFICATIONS

MT372D (4-WD)

MT372 (2-WD)

ENGINE

2-cylinder, water-cooled, overhead-valve, swirl chamber Diesel engine, 15 Hp/2700 rpm. (Max. Bare Hp), displacement 669 cc (40.8 cu. in.), compression ratio 20 : 1.

ENGINE ACCESSORIES

Dry paper element cyclone type air cleaner, 12-volt electrical starter system, paper element cartridge type oil filter, foot throttle, thermostat.

CLUTCH

Dry single disc clutch.

TRANSMISSION

Selective sliding gear, dual range 8-speed, differential gear, differential lock.

TRAVELLING SPEEDS

Min. speed 1.06 km/h (0.66 mph), max. speed 12.01 km/h (7.46 mph) for forward at 2700 engine rpm.

POWER TAKE OFF

Multi-speed PTO 1-3/8 in. 6-spline SAE standard PTO shaft with over-running clutch, 565, 832 and 1364 rpm at 2700 engine rpm.

BRAKE

Water proof internal expansion drum-type with parking brake.

TREAD

| | 4-WD | | 2-WD | |
|-------|------------------|----|------------------|--|
| Front | 785mm (30.9 in.) | AG | 720mm (28.3 in.) | |
| | 800mm (31.5 in.) | ES | 790mm (31.1 in.) | |
| Rear | 740mm (29.1 in.) | AG | 740mm (29.1 in.) | |
| | and | | and | |
| | 890mm (35.0 in.) | | 890mm (35.0 in.) | |
| | 790mm (31.1 in.) | ES | 790mm (31.1 in.) | |
| | and | | and | |
| | 840mm (33.1 in.) | | 840mm (33.1 in.) | |

TIRES

| | | 4-WD | 2-WD |
|---------|-------|--------|-----------|
| AG Tire | Front | 5-12 | 4.00-9 |
| | Rear | 8-16 | 8-16 |
| ES Tire | Front | 6-12 | 18x7.00-8 |
| | Rear | 9.5-16 | 9.5-16 |

STEERING

Worm and sector steering box for 2-WD.
Ball screw steering box for 4-WD.

SEAT

Deluxe foam rubber seat.

HYDRAULIC SYSTEM

(Live hydraulic system)

Designed output: linkage pump 14.2 l/min (3.8 gpm) at 2700 engine rpm.

Implement control: lift, hold, down, flow control and lift lock.

3-POINT LINKAGE

Category O or I linkage with check chain. 650 kg (1433 lb) lifting capacity at lower link end.

DRAWBAR

Permanent drawbar.

DIMENSIONS

| | 4-WD AG Tire | 2-WD AG Tire |
|------------------|------------------|------------------|
| Length | 1965mm(77.4 in.) | 1960mm(77.2 in.) |
| Width | 960mm(37.8 in.) | 960mm(37.8 in.) |
| Height | 1180mm(46.5 in.) | 1180mm(46.5 in.) |
| Wheel base | 1305mm(51.4 in.) | 1280mm(50.4 in.) |
| Ground clearance | 235mm(9.3 in.) | 270mm(10.6 in.) |
| Weight | 534 kg (1177 lb) | 485 kg (1069 lb) |

ELECTRICAL

12-volt 45 AH battery.

CAPACITIES

| | |
|------------------|----------------------|
| Fuel tank | 15 l (4 gal) |
| Engine oil | 3 l (3 qt) |
| Transmission oil | 12.6 l (3 gal, 1 qt) |
| 4-WD front axle | 2.5 l (5.5 pt) |
| Cooling water | 4.2 l (1 gal, 1 pt) |

STANDARD EQUIPMENT

Thermostat
Pre-heat plug and indicator
Oil pressure indicator
Battery charge indicator
Water temperature indicator
Hour meter
Tachometer
Safety starter switch
Head lamps
Safety cover for fan belt
Foot throttle
Differential lock
Horizontal exhaust with silencer
Fuel level gauge
Oil level gauge
Deluxe seat
Tool box and tool kit
Over-running clutch

OPTIONAL EQUIPMENT

Front PTO
Front wheel weights for 2-WD AG only
Rear wheel weights for all models
Front chassis weight for all models
Vertical exhaust pipe
Hydraulic adapter plate
Working lamp
Flasher lamp
Radiator screen
Rotary tiller

* Specifications are subject to change without notice.



MITSUBISHI AGRICULTURAL MACHINERY CO., LTD.

Inside U.S.A.:

MAM Tractors,
22H, Cragwood Rd., Avenel N.J. 07001
TEL: (201) 388-7888

Outside U.S.A.:

6-3, 3-chome, Kanda Kaji-cho, Chiyoda-ku, Tokyo, Japan
TEL: Tokyo (03) 258-0116 TELEX: 2228052