

**SAME**

**panther**



**4-wheel drive model**  
original «SAME» system

- Improved performance with the SAME four-wheel drive
- Fuel saving with the SAME air-cooled, direct injection engine
- Maximum regularity in work over the years ensured by the SAME automatic linkage control unit



**ENGINE**

Model SAME 985-041  
 Fuel type Diesel  
 Cycle 4 stroke  
 Injection Direct  
 Number of cylinders 5  
 Cylinder arrangement in line  
 Cylinder bore 3.85826 ins ( 98 mm)  
 Stroke 4.72440 ins (120 mm)  
 Displacement 276 cu. ins (4526 cm<sup>3</sup>)  
 Compression ratio 17 : 1  
 Max. power 88 HP - DIN  
 R.p.m. at max. power 2200  
 Max. torque 217 lb. ft (30.0 kpm)  
 R.p.m. at max. torque 1450  
 Cooling air  
 Lubrication forced  
 Injection pumps internal in line  
 Air cleaner dry

**CLUTCH**

Single clutch - Dry, single plate - Mechanically actuated by pedal.

**GEARBOX**

12 forward gears and 3 reverse gears, all synchronized - Extra-reduction available upon request in two styles.

**DIFFERENTIAL LOCK**

Mechanically actuated by pedal with automatic disengagement on releasing pedal.

**BRAKES**

Two brakes acting in oil bath on rear wheels, multiplate (4+4).

**STEERING**

Hydraulic servo-steering.

**POWER TAKE-OFF**

Completely independent at 540 and 1000 r.p.m.

**AUTOMATIC LINKAGE CONTROL UNIT**

Maximum lifting capacity: 6300 lbs (2860 kg) - 4-way directional control valve for external hydraulic functions - 3-point implement coupling, class 2.

**TYRES****2-W.D.**

standard	7.50-18 front tyres	16.9/14-34 rear tyres
optional	7.50-20 front tyres	18.4/15-34 rear tyres
	7.50-18 front tyres	13.6/12-38 rear tyres
	7.50-20 front tyres	23.1/18-26 rear tyres

**4-W.D.**

standard	12.4/11-24 front tyres	16.9/14-34 rear tyres
optional	12.4/11-24 front tyres	13.6/12-38 rear tyres
	13.6/12-24 front tyres	18.4/15-34 rear tyres

**PERFORMANCE**

Speeds in m.p.h. (km/h) with engine at 2200 r.p.m. and with rear tyres 16-9/14-34

1st	0.57 (0.93)	7th	3.50 ( 5.63)	1st rev.	0.95 ( 1.53)
2nd	0.80 (1.29)	8th	4.79 ( 7.71)	2nd rev.	3.02 ( 4.87)
3rd	1.10 (1.77)	9th	5.84 ( 9.39)	3rd rev.	9.64 (15.51)
4th	1.50 (2.42)	10th	8.13 (13.09)		
5th	1.83 (2.95)	11th	11.14 (17.93)		
6th	2.55 (4.11)	12th	15.27 (24.58)		

**DIMENSIONS**

(with rear tyres 16.9/14-34)

	2-W.D.	4-W.D.
Overall length (without rear implement couplings)	146.5 ins (372 cm)	151.8 ins (386 cm)
Overall width	79.9 ins (203 cm)	79.9 ins (203 cm)
Overall height	70.9 ins (180 cm)	70.9 ins (180 cm)
Height to hoodline	59.1 ins (150 cm)	59.1 ins (150 cm)
Ground clearance	23.6 ins ( 60 cm)	16.1 ins ( 41 cm)
Wheel base	98.7 ins (251 cm)	98.7 ins (251 cm)
Front wheel-track minimum	55.1 ins (140 cm)	63.0 ins (160 cm)
maximum	86.6 ins (220 cm)	—
Rear wheel-track minimum	63.0 ins (160 cm)	63.0 ins (160 cm)
maximum	86.6 ins (220 cm)	86.6 ins (220 cm)
<b>WEIGHT</b>		
Weight in running order	7170 lbs (3250 Kg)	7720 lbs (3500 Kg)



2-wheel drive model

# SAME

**SAME S.p.A.**  
24047 Treviglio (Italy)  
Tel. 2781  
Telex: 32472 Sametrac

A cura del Servizio Pubblicità SAME - Mod. 308103930 - Ottobre 1976  
Technical data are subject change and are not binding.

# Agip F.1

the lube-oil  
of our choice



area agent: