

DAEDONG

DK 60 - DK 90

60 - 92 Horsepower Flat Platform and Cabin Tractors



DAEDONG

Model	DK 60 - 60 HP	DK 65 - 65 HP	DK 75 - 75 HP	DK 80 - 82.5 HP	DK 90 - 92 HP
Engine					
Make	Perkins	Perkins	Perkins	Perkins	Perkins
Model	704.3	903.27T	1004.4	1004.42	1004.4T
Type	Diesel	Diesel	Diesel	Diesel	Diesel
Cylinders	4	3	4	4	4
Cooling System	Water Cooled	Water Cooled	Water Cooled	Water Cooled	Water Cooled
Horse Power SAE	60.3 HP @ 2300 rpm	65 HP @ 2250 rpm	75 HP @ 2200 rpm	82.5 HP @ 2300 rpm	92 HP @ 2200 rpm
Displacement	2956cc	2700cc Turbo	3990cc	4233cc	3990cc Turbo
Bore & Stroke	97 x 100 mm	95 x 127 mm	100 x 127	103 x 127	100 x 127
Fuel Tank Capacity	100 Litres	100 Litres	100 Litres	100 Litres	100 Litres

Transmission

Manual Type w/ Sync Shuttle

Number of Speeds	Full Synchro 12 Forward x 12 Reverse (including creeper range)
Shuttle Control	Synchro Forward & Reverse

Travel Speeds and Drive Wheels

Forward Speed	Manual 0.2 – 35 km/h
Reverse Speed	Manual 0.2 – 33 km/h
Drive Wheels	4WD

Power Take Off

Type	Independent with Auto PTO
PTO Engage	Electro Hydraulic – No Clutch
Number of Speeds	2 @ 540 & 750 (Optional 2 @ 540 and 1000)

Brakes & Steering

Steering Type	Hydrostatic Power Steering
Tilt steering	Standard
Type of Brakes	Large Oil Cooled Multi-Disc
Differential Lock	Front & Rear

Hydraulics

3 Point Linkage	Quick Hitch Hook Ends, Category 2				
Leveling System	Electro-Hydraulic with Push Button Control next to Seat and on Wheel Guard				
Pump Capacity Combined	73.3 litres/min	66 litres/min	77.4 litres/min	80.9 litres/min	77.4 litres/min
No. of Hydraulic Ports	2 Double Acting at Rear & 2 Double Acting at Front				
Lift Capacity	3000 kg	2500 kg	3000 kg	3000 kg	3000 kg
Position Control	Standard				
Draft Control	Standard				

Dimensions

Overall Length	3865 mm	3865 mm	3958 mm	3958 mm	3958 mm
Overall Width	1800 mm	1800 mm	1980 mm	1980 mm	1985 mm
Overall Height	2560 mm	2560 mm	2590 mm	2590 mm	2610 mm
Wheel Base	2048 mm	2048 mm	2142 mm	2142 mm	2142 mm
Ground Clearance	370 mm	370 mm	425 mm	425 mm	425 mm
Weight	3120 kg	3250 kg	3690 kg	3820 kg	3900 kg
Ag Tyres: Front	11.2 - 20	11.2 - 20	12.4 - 24	12.4 - 24	12.4 - 24
Rear	16.9 - 30	16.9 - 30	18.4 - 34	18.4 - 34	18.4 - 34

Other Features / Options

Extreme Turning Circle	Standard
Full Lighting	Standard
Operator Platform	Flat & Rubber Mounted with no obstacles
Key Stop	Standard
Fold Down Safety Frame	Standard
No Tool Quick Removal Loader	Optional

Optional Cabin

Type	High Visibility
Ventilation	Air Conditioning
Noise Level	77Db

Australian Distributor

Agriculture Holdings Pty Ltd,
21 Silicon Place, Tullamarine 3043, Australia.
Phone +61 3 9335 6575 Fax +61 3 9335 5232
Email agihold@agricultr.com.au
www.daedong.net.au

New Zealand Distributor:

Power Farming (Wholesale) Ltd,
PO Box 6, Morrinsville, New Zealand
Phone +64 7 902 2200 Fax +64 7 902 2201
Email daedong@powerfarming.co.nz
www.nzag.co.nz

Your contact: