

TG5470



Engine	Type	Diesel, 4 Cyl, water cooled
	Output (Net (PS @ rpm)	46.0 @ 2800
	Displacement (cc)	2197
	Fuel tank capacity (l)	50.0
Transmission	Number of forward speeds	12
	Forward speed (km/h)	0.36 - 29.06
	Number of reverse speeds	12
	Reverse speed (km/h)	0.33 - 24.46
	Driven wheels	2WD / 4WD
	Differential lock	Std. / Pedal
	Brakes	Wet disks
Transmission Options -	Powershuttle with 16x16 speed Powershuttle with 4 speed powershift (3 ranges)	
PTO	Type	Clockwise rotation, can be engaged under load
	Shaft	1 3/8" 6-spline
	Rotational speed (rpm)	540 - 1000
Hydraulics	Pump capacity (L/min.)	29.2
	Position control	Standard
	Draft control	Standard
	Rear linkage type	Category 1
	Lift capacity (kg)	1580
	Steering type	Hydrostatic
Electrical	Battery (Ah)	72
Dimensions	Overall length (mm)	3450
	Overall width (mm)	1560
	Overall height (mm)	2770
	Wheelbase (mm)	1900
	Ground clearance (mm)	400
	Weight (kg)	1645
	Agri. tyres front	9.5 - 16
	Agri. tyres rear	13.6 - 28
	Turf tyres front	29 x 12.00 - 15
Turf tyres rear	475 / 65D - 20	

Note: The technical features may be altered without prior notice.