

ISEKI TM3200/TM3240

TM3200

TM3240



 **ISEKI**
Quality and Performance you can Trust

		TM3200		TM3240	
		Mech	HST	Mech	HST
Engine	Type	Diesel, 3 Cyl, water cooled		Diesel, 3 Cyl, water cooled	
	Output (Net (PS @ rpm)	19.5 @ 2500		22 @ 2600	
	Displacement (cc)	1123		1123	
	Fuel tank capacity (l)	25.0		25.0	
Transmission	Number of forward speeds	-	2	-	2
	Forward speed (km/h)	21.1		20.1	
	Number of reverse speeds	-	2	-	2
	Driven wheels	4WD		4WD	
	Differential lock	STD		STD	
	Brakes	Wet Disk		Wet Disk	
PTO	Type	Clockwise rotation, can be engaged under load Rear/Mid			
	Shaft	1 3/8" 6-spline		1 3/8" 6-spline	
	Rear PTO speed (rpm)	546 @ 2500	565 @ 2500	567 @ 2600	587 @ 2600
	Front PTO speed (rpm)	2045 @ 2500	1936 @ 2500	2127 @ 2600	2013 @ 2500
Hydraulics	Pump capacity (L/min.)	19.8		20.6	
	Position control	Standard		Standard	
	Rear Linkage Type	Category 1		Category 1	
	Lift capacity (kg)	540		540	
	Steering type	Hydrostatic (power)		Hydrostatic (power)	
Dimensions	Overall length (mm)	2680		2680	
	Overall width (mm)	1160		1230	
	Wheelbase (mm)	1520		1520	
	Ground clearance (mm)	280		280	
	Weight (kg)	710		710	
	Agri. tyres front	5.00 - 12		5.00 - 12	
	Agri. tyres rear	8.18		9.5 - 16	
	Turf tyres rear	20.5 x 8.00 - 10		23.0 x 10.50 - 12	
Turf tyres front	29 x 12.00 - 15		31.5 / 75D - 15		

Note: The technical features may be altered without prior notice.

