

TXG23



Comfort and reliability

The 22.5 ps Iseki water-cooled 3-cylinder diesel engine is mounted to the compact body. By HST transmission, the operator can change forward and reverse speeds without the clutch pedal. Also, slant bonnet allows a front view and levers are located to each side of operator's seat for safety. A spacious flat deck provides ample space for the operator's feet.



Performance

Standard Rear 3-point linkage, Rear PTO, Mid PTO, and Mid-mount linkage gives versatility in every job undertaken. By independent PTO and hydrostatic power steering, efficient operation is possible. 4WD gives suitable traction even on slippage or slope.



Utility

The Iseki TXG tractor has a heavy-duty frame and can be equipped with various implements such as mowers, a front loader, back-hoe or high-dump grass collector. Its combined features of garden tractor and compact tractor benefits the operator in both cost and performance.



Engine	Type	Diesel, 3 Cyl, water cooled
	Output (Net (kW @ rpm))	16.5 @ 2600
	Output (Net (PS @ rpm))	22.5 @ 2600
	Displacement (cc)	1123
	Fuel tank capacity (l)	21.0
Transmission	Type	Hydrostatic
	Number of forward speeds	2
	Forward speed (km/h)	0 - 14.7
	Number of reverse speeds	2
	Reverse speed (km/h)	0 - 11.0
	Driven wheels	2 / 4WD
	Differential lock	Std. / Pedal
	Brakes	Multi wet disk
PTO	Type	Can be engaged under load
	Shaft	1 3/8" 6-spline
	Rotational speed of rear (rpm)	540
	Rotational speed of mid (rpm)	2000
Hydraulics	Pump capacity (L/min.)	23.1
	Position control	Direct control
	Draft control	-
	Rear linkage type	Category 1
	Lift capacity (kg)	540
	Steering type	Power-assisted
Electrical equipment	Battery (Ah)	36
Dimensions	Overall length (mm)	2480
	Overall width (mm)	1190
	Wheelbase (mm)	1450
	Ground clearance (mm)	170
	Weight (kg)	630
	Agri. tyres front	18 x 8.50 - 8
	Agri. tyres rear	26 x 12.00 - 12
	Turf tyres front	18 x 8.50 - 8
	Turf tyres rear	26 x 12.00 - 12

Note: The technical features may be altered without prior notice.