



СССР МОСКВА

ТРАКТОРОЭКСПОРТ

TRACTOR
T-25A1



TRACTOR T-25A1

Universal wheeled tractor T-25A1 is designed for inter-row cultivation of vegetable gardens and orchards, seedbed preparation, sowing, vegetable planting, crop attendance, hay harvesting, tillage and transport jobs as well as for beltwork.

The ingenious design of the tractor provides three wheelbase and ground clearance settings to suit the various working conditions. The controls, seat and gearbox are constructed for convenient operation in reverse.

The machine features unorthodox design, small size with a relatively powerful engine, straightforward maintenance and high reliability.



TRAKTOROEXPORT

21/5, Kuznetsky most, 103031, Moscow, USSR

Telephone: 221-56-07, 223-13-38

Telex: 7273, 7274

Specifications

Overall dimensions, mm:

	Normal Setting	High Setting	Low Setting
Length (with weights and linkage)	3110	2965	2758-3192
Height over cowl	1350	1420	1200
Height over canopy	2340	2410	2190
Width (with minimum track)		1370	
Track (adjustable in 100 mm steps):			
Front wheels 6.00-16"		1200-1400	
Rear wheels 9-32"		1100-1500	
Wheelbase	1775	1630	1423-1837
Ground clearance (under brake sleeves)	587	657	450
Travel speed, km/hr:		Forward	Reverse
1st		6.4	6.4
2nd		8.1	8:1
3rd		9.4	9.4
4th		11.9	11.9
5th		14.9	14.9
6th		21.9	21.9
Underdrive, 1st			1.79
Underdrive, 2nd			2.64
Underdrive, 1st (at 900 engine rpm)			0.90

Engine

Type	Diesel, air-cooled, direct injection
Number of cylinders	2
Bore, mm	105
Stroke, mm	120
Horsepower at 1800 rpm (DIN), hp	25
Specific fuel consumption, g/bhp-hr	180 max.
PTO	Transmission drive
Speed at 1775 engine rpm, rpm	540
Turning radius, m	3-3.5
Weight, kg:	
Design	1600
Working	1800

Optional extras:

drive pulley, auxiliary weights, trailer brake control system, canopy, front fenders, tyres 10-28", driver's toolkit, drawbar, hydraulic hook.

The specifications are subject to change without notice.