

CASE IH
AGRICULTURE

MAXXFARM SERIES TRACTORS



> Powerful **water-cooled 4 cylinder** engine delivers low fuel consumption and efficient power transfer

> **Excellent visibility** and one-touch bonnet with gas strut ensures easy maintenance and servicing

> **Super tight 55° steering angle** makes operating easy in narrow crop rows, yards and field edges.

**POWERFUL PERFORMANCE.
EASY TO OPERATE.**



> **Powerful Synchro Shuttle** transmissions enable fast operation in field tasks and front end loader work

> **Comfortable, well-designed** operator console with easy to use controls that save time and effort

> **High-performance hydraulics** with separate main pump and steering pump for high-load work.

PUT A MAXXFARM ON YOUR FARM

The new MAXXFARM tractors series brings the ideal small tractor range for farmers and professionals who demand more from their equipment, their assets and themselves.

Four all-new models come with the features you would expect in a large tractor such as super-tight turning angle, high ground clearance and superb visibility. The superior finger-trip Shuttle Lever control enables easy forward-reverse direction changes, essential when working in compact spaces and moving around obstacles. Availability in ROPS or luxury cab models with air-conditioning gives you the choice of features to obtain maximum access while offering great comfort for long days in the cab.

With a long list of performance-enhancing features, you'll be sure of a reliable, powerful farm machine backed by Case IH dealers and support services.

The hydrostatic transmission available on the MAXXFARM 35 provides effortless changes in speed from standstill to maximum.



Model	Engine Power kW (hp)	Transmission
MAXXFARM 35	28 (38)	12 x 12 or Hydrostatic
MAXXFARM 40	30 (41)	16 x 16
MAXXFARM 50	35 (47)	16 x 16
MAXXFARM 60	42 (57)	16 x 16



Excellent turning circle



Easy to use controls



Easy service access

CASE IH. FOR THOSE WHO DEMAND MORE.

SPECIFICATIONS

SPECIFICATIONS	MAXXFARM 35		MAXXFARM 40	MAXXFARM 50	MAXXFARM 60
ENGINE					
Gross Output kW (hp)	28 (38)		30 (41)	35 (47)	42 (57)
No. Of Cylinders	4		4	4	4
Displacement (cc)	1758		2311	2505	2505
Fuel Tank Size (L)	32		40	40	60
PTO					
PTO Speed (rpm)	540		540	540	540/750/1000
PTO Power kW (hp)	25 (34)		26 (36)	30 (41)	35 (47)
Control	Electro-Hydraulic		Electro-Hydraulic	Electro-Hydraulic	Electro-Hydraulic
POWER TRAIN					
Transmission	12 x 12	Or Hydrostatic	16 x 16	16 x 16	16 x 16
Speed Range (km/h)	1.3 - 26	0 - 25	1.1 - 26	1.1 - 27	1.2 - 28
Shuttle Function	Synchro Shuttle	Pedal	Synchro Shuttle	Synchro Shuttle	Synchro Shuttle
Brake Type	Wet, MultiDisc		Wet, MultiDisc	Wet, MultiDisc	Wet, MultiDisc
HYDRAULICS					
Lift Capacity (kg)	1188		1250	1250	1750
Remote Valves	2		2	2	2
Steering Type	Power Hydraulic		Power Hydraulic	Power Hydraulic	Power Hydraulic
DIMENSIONS (APPROX)					
Height (mm)	2353		2415	2447	2650 (ROPS) 2403 (CAB)
Length (mm)	2987		3192	3192	3777
Tread (mm)	1059		1100	1100	1426 - 1666
Ground Clearance (mm)	330		355	387	390
Weight (without ballast) (kg)	1230		1625	1625	2265 (ROPS) 2470 (CAB)

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. Case IH is a registered trademark of CNH Australia Pty Ltd. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Australia Pty Ltd, are the property of those respective companies. CNH Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.