



SGR 19

20 Horsepower Hydrostatic



ISEKI SGR 19

Specifications

Engine

Type	Diesel
Cylinders	3
Cooling System	Water Cooled
Horse Power	20 HP @ 2900 rpm
Displacement	928 cc
Fuel Tank Capacity	18.5 Litres
Chassis	Heavy Duty Cast Steel

Transmission

Type	Hydrostatic
Hydrostatic Control	2 Foot Pedal
Forward Speed	0 - 17 km/h
Reverse Speed	0 - 10 km/h
Drive Wheels	2WD
Differential Lock	Standard

Steering & Brakes

Steering Type	Hydraulic Power Steering
Type of Brakes	Wet Disc

Dimensions

Overall Length	1935 mm
Overall Width	1100 mm
Overall Height	1265 mm
Tyre Size / Front	210 / 65D - 8
Rear	250 / 60D - 14
Weight without Deck	400 kg

Mower Decks

Type	Rear Discharge or Mulching
Number of Blades	3
Cutting width	48 or 54 inches
Cutting Height	25 - 120 mm
Deck Material	Super High Density Long Life Cast Steel
Deck Maneuverability	Fully Contouring with Roller Wheels
Mower Lift	Power Hydraulic
Deck Drive	PTO (Shaft) Driven
Deck Thickness	3.6 mm

Catcher Unit

Type	Rear Discharge Catcher
Catching Method	PTO (Shaft) Driven Blower
Dumping Method	Power Hydraulic
Height of Dump	1800 mm
Dumping Capacity	500 Litres

Other Features

Extreme Turning Circle	Standard
Headlights	Standard
Operator Platform	Flat with no obstacles
Access for Maintenance	Rear Guards with Seat & Bonnet Lift
Extra Large Turf Tyres	Standard
Hour Metre	Standard
Fuel Tank Gauge	Standard
Rear PTO	Optional
Remote Control Valve	Optional



Extra strength tractor with heavy duty front axle and heavy duty deck.



Power steering, flat platform, diff lock and wet brakes gives operator maximum comfort, traction and safety.



Optional power assisted rear discharge catcher with high lift.



Call Free 0800 ISEKINZ
473 546

Visit our website nzag.co.nz