

KUBOTA

Two wheel Drive
\$6995
205 S/Frame
x Stock

DIESEL L295DT

TRACTOR

New, more powerful tractor for improved work efficiency!

- Compact and maneuverable body but with all the features of a big tractor.
- Quiet, low-vibration, 3-cylinder diesel engine for real lugging power.
- Performance of bigger tractors but at a fraction of their cost.
- Total quality control and the latest manufacturing facilities assure long tractor life and superior dependability.

**4wheel
drive**



Very efficient tractor with 4-wheel drive has features similar to large tractors and is great for regular commercial landscaping and small farming.

Category 1 3-point hitch accomodates a full line of implements for mowing, cultivating, tilling, hauling, lifting and many other uses.

Features

The new KUBOTA L295DT is a more powerful, low-vibration 3-cylinder diesel tractor with all the features of bigger tractors. It speeds up work and increases efficiency.

- 4-wheel drive
 1. Well-balanced power train
 2. Change from 4 to 2-wheel drive possible
 3. Greater traction and lugging power
 4. Greater stability
 5. Rotary-tilling is easier even on hard ground.
- Dependable compact tractor built in the world's most automated factory.
- Quiet, 3-cylinder, water-cooled diesel engine for reliable power.
- Fuel costs are about half those of the same class gasoline engine.

- Tread is adjustable in rear with farm tires.
- Automatic fuel injection and improved combustion greatly reduce smoke.
- Versatile transmission for all kinds of work: 8 forward and 2 in reverse.
- Constant mesh gears for easy shifting between 1st, 4th, 5th and 8th.
- Differential lock to be used for extra traction on slippery ground.
- Rear PTO with 3 speeds for greater work efficiency.
- PTO shaft in front.
- Power hydraulic lift with convenient position and draft control.
- Auxiliary hydraulic tap.
- Independent wet disc brakes that resist wear.
- Ultra simple maintenance.
- Wider, more comfortable seat with adjustable spring.

Specifications

Model KUBOTA L295DT

Dimensions:

Total length.....	119-1/2 inch (3,035mm)
Total width.....	56-1/4 inch (1,430mm)
Total height.....	56-1/2 inch (1,435mm)
Wheel base.....	65-3/8 inch (1,660mm)
Wheel tread (front).....	43-1/4 inch (1,100mm)
(rear).....	44-58-5/8 inch (1,120-1,490mm)
Ground clearance.....	12-3/8 inch (315mm)
Weight (with 3-point hitch).....	2,601 lbs. (1,180 kg)

Engine:

Vertical, water-cooled, 4-cycle, 3-cylinder diesel engine	
Max. bare horsepower.....	30HP (22.4kw) at 2,800 rpm
Piston displacement.....	79.27 cu. in. (1,299cm ³)

Travel speed:

Forward	First	0.85 mph (1.40 km/h)
	Second	1.13 mph (1.82 km/h)
	Third	1.62 mph (2.61 km/h)
	Fourth	3.03 mph (4.88 km/h)
	Fifth	3.75 mph (6.04 km/h)
	Sixth	4.87 mph (7.85 km/h)
	Seventh	7.00 mph (11.27 km/h)
	Eighth	13.07 mph (21.04 km/h)
Reverse	First	1.48 mph (2.38 km/h)
	Second	6.38 mph (10.27 km/h)

(Creep; optional)

Forward	First	0.10 mph (0.16 km/h)
	Second	0.13 mph (0.21 km/h)
	Third	0.19 mph (0.31 km/h)
	Fourth	0.36 mph (0.57 km/h)
	Fifth	0.44 mph (0.71 km/h)
	Sixth	0.57 mph (0.92 km/h)
	Seventh	0.82 mph (1.32 km/h)
	Eighth	1.54 mph (2.47 km/h)
Reverse	First	0.17 mph (0.28 km/h)
	Second	0.75 mph (1.21 km/h)

Power take-off (SAE 1-3/8 in.)

(at engine speed 2,430 rpm)	
Rear PTO speed	First 540 rpm
	Second 702 rpm
	Third 1,007 rpm
Front PTO speed.....	2,800 rpm
Lifting capacity at lower link end.....	2,051-2,866 lbs. (930-1,300 kg)

Tires:

Farm tires	Front	7-16
	Rear	12.4-24

Standard equipment:

Two front headlights, Three-speed rear PTO shaft with one-way clutch and PTO guard, Front PTO shaft, Differential lock device, 12V battery, Horizontal muffler, Air cleaner, Fuel tank (9.2 gal.=35 lits.), Rear fenders, Foot rests, Safety starting switch, 3-point hitch (Category 1), Hydraulic pump and provisions for additional outlet, Parallelogram seat-suspension, Swing drawbar.

Operation control:

Brake pedals, Clutch pedal, PTO lever, Gear shift lever, Engine stopping lever, Hydraulic control lever with position, Parking brake rod, Foot and hand accelerator, Front wheel power lever.

Instrument panel:

Hour meter with oil pressure warning lamp, Battery charge lamp and engine tachometer, Compression release knob and glow plug for cold starting, Main switch, Starting switch.

Optional equipment:

Tool box, Electromagnetic front PTO clutch, Link drawbar hitch, Rear wheel weight, Fixed hitch, Front bumper weight.



The Basic Necessities Giant

KUBOTA

Kubota, Ltd.

HEAD OFFICE: 22, Funade-cho 2-chome, Naniwa-ku, Osaka, Japan

CABLE ADDRESS: IRONKUBOTA OSAKA

TELEX: 526-7785 KUBOTA J

TOKYO OFFICE: 3, Nihonbashi-Muromachi 3-chome, Chuo-ku, Tokyo, Japan

CABLE ADDRESS: IRONKUBOTA TOKYO

TELEX: 222-3681 KUBOTA J