

Massey Ferguson

1010



Sleek, new contemporary styling. Added performance features. Improved operator comfort. All these and more make the new 16 hp* (11.9 kW) MF 1010 Compact Tractor an exciting addition to the Massey-Ferguson line.

It puts many of the proven features found on Massey's large tractors into a small tractor that's easy and economical to operate.

You can team the new MF 1010 with an MF 218 Mid- or Rear-Mount Mower, an MF 214 Front-End Loader, an MF 222 Rear Blade or a wide variety of tillage implements and other attachments.

Acreage owners will find it the perfect answer for lawn chores, snow removal and similar jobs. And it's also rugged enough for a variety of full-time uses around institutions, landscaping services, construction sites and similar commercial applications.

2 or 4-wheel drive

If you're going to be using your new MF 1010 Compact Tractor for jobs that don't require a lot of extra traction, then the 2-wheel drive version will be more to your liking.

But if you plan on spending time in mud or snow, on steep slopes or pulling loads that require some added muscle, you'll want to step up to 4-wheel drive power. It's an economical way to increase the efficiency of your MF 1010...and handle more jobs at the same time.

The front wheel drive activating lever is conveniently located next to the operator's seat.

And both the 2 and 4-wheel drive MF 1010 Tractors have the dimensions and maneuverability necessary for working in tight spots where a larger machine would never fit.



3-point linkage accurately controls depth and position of mounted implements. Gives uniform tillage. A 540 rpm PTO increases versatility.

3-cylinder diesel engine.

The new MF 1010 is powered by a 3-cylinder diesel engine for increased operating efficiency and dependability.

Matching your speed to the demands of the job is easy with a 3-speed constant mesh transmission with high/low range. It provides 6 forward and 2 reverse speeds. Differential lock provides extra traction when you need it.

Power for the Category I, 3-point linkage on the MF 1010 is provided by a gear driven hydraulic pump. This pump also provides a flow to an optional spool valve to handle hydraulic powered attachments.

A 540 rpm PTO with overrunning clutch lets you team the MF 1010 with power driven implements. Front PTO capability is ideal for use with a mid-mount mower and other equipment.

The MF 1010 is both easy to own and operate. The foam cushioned seat lets you ride in comfort, reduces fatigue.

A forward tilting hood provides easy access for routine maintenance checks.

*Manufacturer's rated engine horsepower.

Specifications: MF 1010

Horsepower

Manufacturer's estimate @ 2500 rpm:
16 engine hp (11.9 kW).
13 PTO hp (9.7 kW).

Engine

Type: Indirect injection diesel.
Cylinders: 3.
Bore and stroke: 2.75 x 2.95 in. (70 x 75 mm).
Displacement: 52.8 in.³ (865 cc).

Clutch

Type: Single dry plate.
Diameter: 7.2 in. (184 mm).

Transmission

Type: Constant mesh with 6 forward and 2 reverse speeds.

PTO

Type: Transmission driven with overrunning clutch. 540 rpm @ 2365 engine rpm.

Brakes

Type: Mechanical shoe brakes.

Hydraulics

Type: Engine mounted gear pump
3.5 gpm (13.2 L/min).
Linkage: Category I
Adjustable leveling link.

Front tread width

(fixed) agr. tires
2WD: 32.3 in. (820 mm).
4WD: 34.8 in. (885 mm).

Rear tread width

agr. tires
2WD: 32.9 in. (835 mm).
4WD: 38 in. (965 mm).

Front tires

Agricultural: 2WD - 4.50 x 10 F2.
4WD - 5 x 12 R1.
Turf: 2WD, 4WD - 20.5 x 8.00-10 G2 (4 ply).

Rear tires

Agricultural: 2WD, 4WD - 8 x 16 R1.
Turf: 2WD, 4WD - 29 x 12.00-15 G2 (4 ply).

Dimensions

Wheelbase: 50.8 in. (1290 mm).
Length: 85 in. (2155 mm).
Width: 41.9 in. (1064 mm).
Height @ steering wheel: 46.9 in. (1191 mm).
Ground clearance: 10.4 in. (264 mm).
Fuel tank capacity: 3.7 (US) gal., 3.1 (Imp) gal., (14.0 L).



The new MF 1010 is available with a variety of accessories...including high flotation turf tires (shown) on the 2-wheel drive model. Attachments

include the MF 218 Mower, new MF 214 Loader and many more. You can equip your MF 1010 to precisely match your needs. Now that's efficiency.

Turning radius (with brakes):
2WD - 77.6 in. (1970 mm).
4WD - 76 in. (1930 mm).
Shipping weight:
2WD - 1269 lbs. (577 kg).
4WD - 1487 lbs. (676 kg).

Additional features

Single dry element cyclone air filter, glow plug starting aid, oil pressure, engine temperature, low fuel warning and alternator charge lights, hourmeter and tachometer, hand and foot throttles, two position muffler (horizontal or vertical), SMV bracket, tilt-up hood, PTO shield, dual front headlights and rear flashing amber lights, rear red warning light, optional front and rear frame weights.

Field installed accessories

Front PTO with electric clutch, ROPS, SMV emblem, exhaust extension, spark arrestor muffler, single spool double acting valve.

Massey Ferguson reserves the right to change design and specifications of its products without notice or obligation.

We believe in customer satisfaction.

Customer satisfaction is vital to Massey-Ferguson's growth and future prosperity. And the key to customer satisfaction is good customer service. That's why MF has parts distribution centers and service training facilities conveniently located throughout North America. This assures that your MF dealer will have the quality replacement parts and MF trained mechanics you need...when you need them. And that's a good way to protect your investment.

MF
Massey Ferguson

MYERS IMPLEMENT AND MOTOR INC.
INTERSTATE 70
WARRENTON, MISSOURI 63383
PHONE 456-4374