


MF[®] 3300 S & F Series Tractors



Specialty S and F Series Tractors



MASSEY FERGUSON[®]

MF® 3300 S & F Series Tractors

MODEL	3315 S 4WD	3330 S 2WD/4WD	3340 F 2WD/4WD	3350 F 4WD	3355 F 4WD
PERFORMANCE					
Engine hp	54	67	78	88	93
PTO hp	47	60	70	78	82
Max. torque: ft. lbs. (Nm)	141.62 (192.0)	192.51 (261.0)	208.00 (282.0)	267.40 (362.5)	274.40 (372.0)
ENGINE					
Model	Perkins 903-27	Perkins 1004-40	Perkins 1004-42	Perkins 1004-40T	Perkins 1004-40T
Type			Diesel		
Cylinders	3	4	4	4	4
Aspiration	Natural	Natural	Natural	TURBO	TURBO
Displacement in ³ (L)	164.8 (2.7)	244.1 (4.0)	256.3 (4.2)	244.1 (4.0)	244.1 (4.0)
Horizontal Exhaust			horizontal, under footrest		
ELECTRICAL					
Battery			12V - 470A - 100Ah		
Alternator (amps)			65A (85A for cab)		
CLUTCH					
Type	organic	cerametallic	cerametallic	cerametallic	cerametallic
Diameter: in (mm)	11 (280)	12 (305)	12 (305)	12 (305)	12 (305)
TRANSMISSIONS					
Standard			16F/8R		
Optional			20F/10R, 24F/12R (w/ supercreep)		
POWER TAKE-OFF (PTO)					
Type (Hydraulic Ind.)			540/1000 removable shaft with cut-off sensor		
Speed: (PTO rpm @ erpm)			540 rpm @ 1967erpm, 1000 @ 2043erpm		
HYDRAULICS					
Pump type			gear pump		
Total system flow:					
gpm (lpm)	11.6 (44); opt. 15.3 (58)	11.6 (44); opt. 15.3 (58)	13.7 (52); opt. 15.3 (58)	13.7 (52); opt. 15.3 (58)	13.7 (52); opt. 15.3 (58)
Max. pressure: psi (bar)			2610 (180)		
Auxiliary valves		2 (std.) 3 (opt.)	spool valves and/or 2 (opt.) front spool valves		
3-POINT HITCH					
Functions			mechanical control (electronic control opt.)		
Type			ball ends (claw type opt.)		
Max. flow: gpm (lpm)	11.6 (44)	11.6 (44)	13.7 (52)	13.7 (52)	13.7 (52)
Max. pressure: psi (bar)			2610 (180)		
Lift capacity @ ball ends: lbs (kg)			5290 (2400)		
STEERING/BRAKES					
Steering type			Hydrostatic		
Brake type & plates			wet discs		
AXLE					
2WD front-type		adjustable	adjustable		
4WD front-engagement			electrohydraulic		
Final reduction			Rear-inboard planetaries, Front-outboard planetaries		
TIRES					
Front tires	240/70R16	6.50/16 - 2WD 240/70R16 - 4WD	7.50/16 - 2WD 280/70R18 - 4WD	280/70R18	280/70R18
Rear tires	360/70R24	12.4/R28 - 2WD 360/70R24 - 4WD	13.6/R28 - 2WD 420/70R24 - 4WD	420/70R24	420/70R24
WEIGHTS & DIMENSIONS					
2WD					
Total weight: lbs (kg)		4740 (2150)	4740 (2150)		
Total weight: w/ cab lbs (kg)		5115 (2320)	5115 (2320)		
Wheelbase: in (mm)		81.9 (2080)	81.9 (2080)		
Overall length: in (mm)		153 (3885)	153 (3885)		
Min. width: in (mm)		46.8 (1189)	55.2 (1402)		
Ground clearance: in (mm)		10.6 (270)	15.0 (380)		
Height over ROPS: in (mm)		86.6 (2200)	87.8 (2230)		
4WD					
Total weight: lbs (kg)	4740 (2150)	5181 (2350)	5181 (2350)	5181 (2350)	5181 (2350)
Total weight: w/ cab lbs (kg)	5115 (2320)	5556 (2520)	5556 (2520)	5556 (2520)	5556 (2520)
Wheelbase: in (mm)	78.7 (2000)	82.7 (2100)	82.7 (2100)	82.7 (2100)	82.7 (2100)
Overall length: in (mm)	143.7 (3650)	147.6 (3750)	147.6 (3750)	147.6 (3750)	147.6 (3750)
Min. width: in (mm)	46.8 (1189)	46.8 (1189)	55.2 (1402)	55.2 (1402)	55.2 (1402)
Ground clearance: in (mm)	8.9 (225)	8.9 (225)	14.0 (355)	14.0 (355)	14.0 (355)
Height over ROPS: in (mm)	86.8 (2200)	86.8 (2200)	87.8 (2230)	87.8 (2230)	87.8 (2230)
CAPACITY					
Fuel tank: gal (l)	11.9 (45)	17.3 (65.5)	17.3 (65.5)	17.3 (65.5)	17.3 (65.5)

OTHER STANDARD FEATURES

Spring suspension seat
 Foldable ROPS (Platform Models)
 Safety start
 Safety shutoff (Key)
 Electric Fuel shutoff
 Gauges — RPM, Fuel level, Coolant temperature
 Horn
 SMV

