

New Holland High Clearance Tractors 8010



Powerful and efficient

The New Holland Model 8010 high-clearance tractor has the power and clearance you need to work in valuable crops without damaging them.

The big, 456 cubic inch New Holland engine delivers 96 PTO horsepower--with the low-end torque you need for pulling heavy loads through mud or sandy soils. Four wheel drive is standard.

Ample crop clearance of 25 inches under the four wheel drive front axle, and 29 inches at the drawbar elimi-

nates crop damage.

Two transmissions are available: a 12x3 constant mesh that includes creeper gear and a 16x4 DualPower™ with creeper available through dealer installation. The DualPower transmission features a power shift in each of the forward gears, allowing you to instantly decrease ground speed and increase torque for pulling through tough spots.

A hydraulic flow of 9.3 gpm (17.4 gpm with the optional dealer installed

package) lets you drive hydraulically actuated implements or sprayers. Two remotes are available as standard equipment.

A roomy operator's deck allows easy entry and exit. And a heavy duty step and grab rails contribute to operator safety.

Put a New Holland "8010" high-clearance tractor to work in your fields. And get the performance you need.

Specifications

MODEL	8010
Engine	6N
PTO Horsepower (Kw)	96(72)
Displacement cu in (L)	456(7.5)
TRANSMISSIONS	12x3 Constant Mesh (8x2 w/creeper) 16x4 DualPower™ (Creeper-DIA)
HYDRAULICS	
Hydraulic flowgpm(L/m)	9.3(35.2), DIA: 17.4(65.9)
Remotes	Two standard
FEATURES	
FWD	Standard
Rear axles	Dropped for maximum clearance
Ground clearance in(cm)	FWD Axle 25(64) Drawbar 29(74)
PTO	
Type	Independent
Speed	540/1000
3-POINT	
Lift capacity lbs(Kg)	4200(1905)
Position/Draft control	Standard
Sensing	Top Link
Check chains	Standard
Rigid link ends	Standard
TIRES	FRONT REAR 13.6x38 R2 13.6x38 R2
AXLE TRACK WIDTH in(cm)	72(183) to 84(213)
OVERALL WEIGHT	
Mfgr. Est.) lbs(Kg)	9100(4128)

DualPower is a trademark of New Holland, inc.

YOUR NEW HOLLAND DEALER



NEW HOLLAND

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

© 1996 New Holland North America, Inc.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.

31801010 • 99710 • API • PRINTED IN U.S.A.