

FRUTTETO II 55-70-75-90-100



**NEW ENGINES EURO II, 1000 SERIES,
WITH LIQUID COOLING**

SYNCHRO POWER GEARBOX

**40 KM/H HYDROSTATIC BRAKING SYSTEM
ON ALL-WHEELS**

FRONT LIFT AND P.T.O.

www.same-tractors.com
 **SAME**[®]
Rely on us.

TECHNICAL SPECIFICATIONS

FRUTTETO II 55

FRUTTETO II 70

FRUTTETO II 75

FRUTTETO II 90

FRUTTETO II 100

Version	4WD	4WD	2WD	4WD	4WD	4WD
ENGINE SAME	1000.3 W EURO II	1000.3 WT EURO II	1000.4 W EURO II	1000.4 WT EURO II	1000.4 WT EURO II	1000.4 WT EURO II
Cylinders/Displacement	n°/cm³	3/3000	3/3000	4/4000	4/4000	4/4000
Aspiration		Natural	Turbo	Natural	Turbo	Turbo
Max. homologated power (2000/25/CE)	HP/kW	55/40,5	70/51,5	74/54,5	87/64	95/70
Max. homologated power (ECE R24.03)	HP/kW	52/38,5	67/49,5	70/51,5	83/61	90/66
Nominal engine speed	rpm	2350	2350	2350	2350	2350
Max. torque	Nm	190	243	240	324	351
Max. torque engine speed	rpm	1400-1600	1400-1600	1400-1600	1400-1600	1400-1600
Torque backup	%	23	22	15	31	31
Cooling				liquid-oil		
Engine control				mechanical		
Air cleaner				electronic		
Silencer underhood				dry with safety cartridge		
Fuel tank capacity	litres			with lateral exhaust		
				40 with rear tank		
				30 with tank under platform		

DIMENSIONS AND WEIGHTS: (with rear tyres)	360/70 R 24	360/70 R 24	380/70 R 24	380/70 R 24	420/70 R 24	
Max. length	mm	3040	3040	3190	3190	3205
Width min. - max.	mm	1450-1740	1450-1740	1470-1760	1470-1760	1562-1960
Height with roll-bar	mm	2070	2070	2090	2090	2110
Max. height at cab	mm	2130	2130	2140	2140	2155
Max. height at engine hood	mm	1120	1120	1145	1145	1160
Max. height at steering wheel	mm	1220	1220	1240	1240	1260
Ground clearance	mm	265	265	285	285	300
Wheelbase	mm	1950	1950	2080	2080	2080
Front track min. - max.	mm	1210-1380	1210-1380	1080-1280 1210-1380	1210-1380	1040-1405
Rear track min. - max.	mm	1090-1380	1090-1380	1090-1380	1090-1380	1140-1540
Minimum steering radius without braking	mm	3560	3560	3400 3760	3760	3800
Weight with roll-bar	kg	2165	2230	2150 2330	2355	2410
Weight with cab	kg	2315	2380	2300 2480	2505	2560

DIMENSIONS with rear tyres	380/70 R 20	420/70 R 28	
Min. - max. Width	mm	1460-1845	1560-1960
Max. height at engine hood	mm	1100	1240
Max. height at steering wheel	mm	1170	1330
Ground clearance	mm	385	440

TRANSMISSION	
Gearbox clutch	mechanically operated
Mechanical gearbox, 4 synchronised gears, 3 gear ranges (min. speed: 1.06 km/h)	12 FWD + 12 REV
Mechanical gearbox, 4 synchronised gears, 4 gear ranges with creeper (min. speed: 0.31 km/h)	16 FWD + 16 REV
SYNCHRO POWER gearbox (2 power gears), 4 synchronised gears, 3 gear ranges (min. speed: 0.93 km/h)	24 FWD + 24 REV
SYNCHRO POWER gearbox (2 power gears), 4 synchronised gears, 4 gear ranges with creeper (min. speed: 0.33 km/h)	32 FWD + 32 REV
Max. speed	km/h 40
Shuttle	mechanical, synchronised
Rear differential lock	mechanically operated electro-hydraulically operated
Lubrication	forced

REAR P.T.O.	
Speed	rpm 540-540 ECON rpm 540-1000
Operation	synchronised P.T.O. electro-hydraulically operated, push-button control

FRONT P.T.O. (4WD versions only)	
Clutch	multiple discs in oil bath
Speed	rpm 1000
Operation	electro-hydraulically operated, push-button control

BRAKES AND STEERING	
Braking system	all wheel braking, discs in oil bath on all 4 wheels, hydrostatically operated
Parking brake	independent
Trailer braking	hydraulic braking valve
Hydrostatic steering	Load Sensing, adjustable steering wheel
Steering angle	2WD/4WD 70°/55°

12 FWD + 12 REV GEARBOX - SPEEDS IN KM/H AT AN ENGINE SPEED OF 2350 RPM WITH 380/70 R 24 REAR TYRES																
	1 L	2 L	3 L	1 M	4 L	2 M	3 M	1 F	4 M	2 F	3 F	4 F				
LOW	0,33	0,52	0,78	1,01	1,19	1,56	2,36	3,04	3,56	4,70	7,10	9,14	10,70	14,10	21,31	32,12
HIGH	0,40	0,62	0,94	1,21	1,42	1,88	2,84	3,65	4,28	5,64	8,52	10,96	12,84	16,92	25,57	38,54

SYNCHRO POWER GEARBOX WITH CREEPER 32 FWD + 32 REV - SPEEDS IN KM/H AT AN ENGINE SPEED OF 2350 RPM WITH 420/70 R 24 REAR TYRES																
	1 L CR	2 L CR	3 L CR	1 L	4 L CR	2 L	3 L	1 M	4 L	2 M	3 M	1 F	4 M	2 F	3 F	4 F
LOW	0,33	0,52	0,78	1,01	1,19	1,56	2,36	3,04	3,56	4,70	7,10	9,14	10,70	14,10	21,31	32,12
HIGH	0,40	0,62	0,94	1,21	1,42	1,88	2,84	3,65	4,28	5,64	8,52	10,96	12,84	16,92	25,57	38,54

The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.

PLEASE NOTE: REVERSE SPEEDS ARE SLIGHTLY HIGHER THAN THE CORRESPONDING FORWARD SPEEDS.

Akros SPECIALISED LUBRICATION FOR SAME



SAME Tractors - v.le Cassani, 15 - 24047 Treviglio (BG) Italy
tel. +39 0363 4211 - www.same-tractors.com

WILSON FARM SERVICES
P.O. BOX 130, EDEN LANE
GISBORNE
PH. 867-2866