

5031/5041 BALERS



Vermeer

Big bale system for smaller horsepower tractors and tight-fisted budgets



5031 The Vermeer 5031, requires a small 40 hp tractor*, harvests up to 700 lb. bales that measure 5 ft. in diameter and 3 ft. wide. The 2410 lb. unit comes equipped with an open throat, easy start design, spring-loaded belt tension, bale size and bale wrap indicators, and a constant velocity PTO for consistent operating speeds, even at 80 degree turns.

A 4-bar floating pick-up with adjustable tines handles windrows up to 36 inches. Optional hay-saver wheels handle the excess.

The 5031 was designed for operations with smaller horsepower tractors and dairy farmers who want easier handling hay packages.



5041 The Vermeer 5041 requires just a minimum 40 hp tractor*, yet harvests bales weighing up to 1000 lbs. and measuring 5 ft. in diameter by 4 ft. wide. The 2660 lb. unit comes equipped with an open throat, easy start design; spring-loaded bale tension; bale size and bale wrap indicators; and a constant velocity PTO for consistent operating speeds, even at 80 degree turns. The unit is available with hydraulic or electric twine tie

The unit also features adjustable belt tracking which "squares" the machine for "true" tracking during the baling operation.

The 5041 was designed to make a mid-sized package, perfect for dairies and smaller haying operations.

5041 Specifications

DIMENSIONS/WEIGHTS (APPROX.)

Length	135in. (343cm)
Height	94in. (239cm)
Width	88in. (224cm)
Total Weight	2660lb. (1160kg)
Drawbar Weight	450lb. (204kg)
Tire Size	27 x 9.50 x 15 LT (Highway rated)

PICK UP

Full 47" (119cm) wide, spring cushioned 5 bar 40 spring steel double tines, rubber mounted, #50 roller chain with radial pin clutch protection.

DRIVE SYSTEM

6-6½" (16.5cm) wide one ply belts, 540/1000 RPM PTO with slip clutch and overrunning protection, #60 roller chain drive, 12" (30cm) Dia drum roller. 4½" (11cm) Dia upper and lower roller with chromed outboard bearings.

BALE SIZE

Diameter	— up to 5ft (152.5cm)
Width	— 4ft (122cm)
Weight	— up to 1200lbs (545kg)

BALE WRAP

Type	— electric
Twine type	— Sisal or plastic
Storage	— four balls

STANDARD EQUIPMENT

Open throat easy start design, single or double belt tension springs, bale size indicator, bale wrap indicator, adjustable cam track, adjustable belt track, adjustable Hi-Lo hitch, floating pick-up with gauge wheel hay saver wheels, 80° wide angle PTO, mechanical tailgate locks, bale counter, steel sprockets, silage knives, bale restrictor plates, full function electronic tie control.

HORSEPOWER REQUIREMENTS

45 hp minimum.

NORWOOD

C.B. Norwood Distributors Limited

Head Office: 888 Tremaine Avenue, Palmerston North, New Zealand
P.O. Box 1265. Telephone (063) 64-920. Telex 32018 Nortrac. Fax (063) 64-939.