



-X704/X754/X804/X854/X904/LX954 series wheeled tractor



LUK Clutch



Multi-Way Hydraulic Output

www.yto.com.cn



YTO GROUP CORPORATION



-X704/X754/X804/X854/X904/LX954 series wheeled tractor

>> Product technical parameters

Model	YTO-X704	YTO-X754	YTO-X804	YTO-X854	YTO-X904	YTO-LX954
Complete Machine Parameters						
Type	4 × 4					
Overall Dimensions(L × W × H) (mm)	4250 × 2145 × 2650		4350 × 2170 × 2740		4350 × 2300 × 2765	4350 × 2100 × 2765
Wheel Base (mm)	2314					
Min. Ground Clearance (mm)	370		430		440	
Min. Operating Weight (Kg)	3540		3675		3920	
Tyre Spec F/R	11.2-24/16.9-30		11.2-28/13.6-38		13.6-24/16.9-34	
Wheel Track F/R(mm)	1569-2005/1500-2100		1630-1960/1500-2100		1562-2000/1520-2120	
Number of Transmission Gears F/R	12/4					
Speed Range (Km/h) F/R	1.54-25.46/4.02-12.07	1.54-25.46/4.02-12.07	1.63-26.82/4.23-12.69	1.64-26.97/4.26-12.76	1.65-27.17/4.28-12.85	2.17-36.74/5.64-17.39
Lifting Force 610mm (KN)	≥ 21.9					
Lifting Force Articulated Point (KN)	25.6					
Engine Parameters						
Model	LR4A3-23	LR4B5-23	LR4B5-23	LR4M5-23	LR4M5-23	LR4A3L-23
Type	4-Cylinder, Vertical, Water Cooled, 4-Stroke, Direct Injection Combustion Chamber, Natural Aspiration					
Displacement (L)	4.33	4.95	4.95	5.13	5.13	4.33
Rated Power/Speed (Kw/rpm)	51.5/2300	55/2300	59/2300	62.5/2300	66.2/2300	70/2300

>> Product Features

- ◎ YTO 4-Cylinder Diesel Engine of UK Racado Technology Applied, Typical of Large Torque Reserve, Vigorous Power, Low Carbon and Environment-Friendly, and Low Fuel Specific Consumption
- ◎ European Technology Applied to Transmission System, 12F+4R (Optional 12F+12R or 24F+8R), Optional Synchronizer Gear Shifting, Able for Smooth Gear Shift so long as not Parked, Characterized by more Handy and Prompt Operation
- ◎ YTO Front Axle of European Technology Used, Reliable and Durable
- ◎ LUK Dual Clutch of Independent Control, Featuring High Reliability, able for Normal Drive of Farm Implement at Gear Shifting of Transmission, of Higher Operating Efficiency
- ◎ Hydraulic Steering System, with Adjustable Steering Wheel, Featured by Handy and Comfortable Control
- ◎ Static Hydraulic Wet, and Disc Brake, Safe and Reliable
- ◎ Synchronized and Independent PTO Double-Speed Power Output, to Meet the Requirements for Matching Multiple Farm Implements
- ◎ Adjustable Single/Double-Acting Multi-Way Valve, 2 or 3 Groups of Hydraulic Outputs, Typical of Strong Adaptability
- ◎ Fully-Enclosed Cab, with Wide Visibility, Characterized by Nice Appearance, Comfort, and Luxury, and Optional Installation of heater and Air Conditioner



Add: 154, JIANSHE ROAD, LUOYANG, HENAN, CHINA P.C.: 471004

Tel: (86)379-62799000 Fax: (86)379-62799099 Http: //www.yto.com.cn E-mail: gm@yto.com.cn