

# • Out Of This World



# UNIVERSAL 533

<p><b>ENGINE</b> 4 Stroke Diesel Direct Injection 3cy 2696cc Capacity Bore x Stroke = 102 x 110mm 56HP Max (53 Din) Max Torque = 162NM @ 1400 Rotary CAV Fuel Pump Oil Bath Air Cleaner with Pre Cleaner</p>	<p><b>TRANSMISSION</b> 12F x 3R Fully Synchronmesh 279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">L</td> <td style="text-align: center;">M</td> <td style="text-align: center;">H</td> <td style="text-align: right;">Range</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">0.7</td> <td style="text-align: center;">2.1</td> <td style="text-align: center;">7.8</td> <td></td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">1.0</td> <td style="text-align: center;">3.2</td> <td style="text-align: center;">11.7</td> <td></td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">1.5</td> <td style="text-align: center;">4.7</td> <td style="text-align: center;">17.1</td> <td></td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">2.0</td> <td style="text-align: center;">6.1</td> <td style="text-align: center;">22.2</td> <td></td> </tr> <tr> <td style="text-align: center;">R</td> <td style="text-align: center;">1.0</td> <td style="text-align: center;">3.1</td> <td style="text-align: center;">11.2</td> <td></td> </tr> </table> <p style="text-align: center;">Heavy Duty Rear Axle</p> <p style="text-align: center;">BRAKES - Oil immersed wet discs</p> <p style="text-align: center;">DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	0.7	2.1	7.8		2	1.0	3.2	11.7		3	1.5	4.7	17.1		4	2.0	6.1	22.2		R	1.0	3.1	11.2		<p><b>PTO</b> 540/1000 RPM &amp; Ground Drive 279mm PTO Clutch Independant Control</p> <hr/> <p style="text-align: center;">FUEL TANK - 62 litre capacity</p> <hr/> <p style="text-align: center;">STEERING - Hydrostatic steering</p> <hr/> <p style="text-align: center;"><b>FRONT AXLE</b> 4WD — Heavy duty front axle, centre drive epicyclic reduction in front hub. Non spin diff lock. Fully hydrostatic steering. 2WD — Telescopic sliding axle</p>	<p><b>HYDRAULIC SYSTEM</b> Engine Driven Hyd Pump 34 LPM Capacity Position/Draft Control Cat II 3 Point Linkage Max Lift 2150kg Two DIA Remotes Std Operating Pressure 2600 psi</p>	<p><b>DIMENSIONS</b> <b>533 DT</b> Wheelbase 2130mm Overall Length 3640mm Height 2450mm Weight 2660kg Wheel Equipment: 9.5 x 20 Front, 14.9 x 28 Rear</p> <p><b>533 2wd</b> Wheelbase 2125mm Overall Length 3490mm Height 2450mm Weight 2470kg Wheel Equipment: 650 x 16 Front, 14.9 x 28 Rear</p>
	L	M	H	Range																														
1	0.7	2.1	7.8																															
2	1.0	3.2	11.7																															
3	1.5	4.7	17.1																															
4	2.0	6.1	22.2																															
R	1.0	3.1	11.2																															

# UNIVERSAL 643

<p>4 Stroke Diesel Direct Injection 4cy 3595cc Capacity Bore x Stroke = 102 x 110mm 68HP Max (64 Din) Max Torque = 206NM @ 1400 Rotary CAV Fuel Pump Oil Bath Air Cleaner with Pre Cleaner</p>	<p>12F x 3R Fully Synchronmesh 279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">L</td> <td style="text-align: center;">M</td> <td style="text-align: center;">H</td> <td style="text-align: right;">Range</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">0.9</td> <td style="text-align: center;">2.9</td> <td style="text-align: center;">10.6</td> <td></td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">1.4</td> <td style="text-align: center;">4.4</td> <td style="text-align: center;">16.0</td> <td></td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">2.1</td> <td style="text-align: center;">6.5</td> <td style="text-align: center;">23.5</td> <td></td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">2.7</td> <td style="text-align: center;">8.4</td> <td style="text-align: center;">30.3</td> <td></td> </tr> <tr> <td style="text-align: center;">R</td> <td style="text-align: center;">1.3</td> <td style="text-align: center;">4.2</td> <td style="text-align: center;">15.3</td> <td></td> </tr> </table> <p style="text-align: center;">Heavy Duty Rear Axle</p> <p style="text-align: center;">BRAKES - Oil immersed wet discs</p> <p style="text-align: center;">DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	0.9	2.9	10.6		2	1.4	4.4	16.0		3	2.1	6.5	23.5		4	2.7	8.4	30.3		R	1.3	4.2	15.3		<p>540/1000 RPM &amp; Ground Drive 279mm PTO Clutch Independant Control</p> <hr/> <p style="text-align: center;">FUEL TANK - 62 litre capacity</p> <hr/> <p style="text-align: center;">STEERING - Hydrostatic steering</p> <hr/> <p style="text-align: center;"><b>FRONT AXLE</b> 4WD — Heavy duty front axle, centre drive epicyclic reduction in front hub. Non spin diff lock. Fully hydrostatic steering. 2WD — Telescopic sliding axle.</p>	<p>Engine Driven Hyd Pump 34 LPM Capacity Position/Draft Control Cat II 3 Point Linkage Max Lift 2150kg Two DIA Remotes Std Operating Pressure 2600 psi</p>	<p><b>643 DT</b> Wheelbase 2270mm Overall Length 3780mm Height 2450mm Weight 2750kg Wheel Equipment: 9.5 x 24 Front, 16.9 x 30 Rear</p> <p><b>643 2wd</b> Wheelbase 2265mm Overall Length 3690mm Height 2420mm Weight 2740kg Wheel Equipment: 750 x 18 Front, 16.9 x 30 Rear</p>
	L	M	H	Range																														
1	0.9	2.9	10.6																															
2	1.4	4.4	16.0																															
3	2.1	6.5	23.5																															
4	2.7	8.4	30.3																															
R	1.3	4.2	15.3																															

# UNIVERSAL 703

<p>4 Stroke Diesel Direct Injection 4cy 3759cc Capacity Bore x Stroke = 102 x 115mm 75HP Max (70 Din) Max Torque = 235NM @ 1400 Rotary CAV Fuel Pump Oil Bath Air Cleaner with Pre Cleaner</p>	<p>12F x 3R Fully Synchronmesh 279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">L</td> <td style="text-align: center;">M</td> <td style="text-align: center;">H</td> <td style="text-align: right;">Range</td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">1.1</td> <td style="text-align: center;">3.4</td> <td style="text-align: center;">10.0</td> <td></td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">1.6</td> <td style="text-align: center;">4.7</td> <td style="text-align: center;">13.7</td> <td></td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">2.0</td> <td style="text-align: center;">5.9</td> <td style="text-align: center;">24.1</td> <td></td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">2.8</td> <td style="text-align: center;">8.2</td> <td style="text-align: center;">24.1</td> <td></td> </tr> <tr> <td style="text-align: center;">R</td> <td style="text-align: center;">1.3</td> <td style="text-align: center;">3.8</td> <td style="text-align: center;">11.3</td> <td></td> </tr> </table> <p style="text-align: center;">Heavy Duty Rear Axle</p> <p style="text-align: center;">Planetary Reductions</p> <p style="text-align: center;">BRAKES — Oil immersed wet discs</p> <p style="text-align: center;">DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	1.1	3.4	10.0		2	1.6	4.7	13.7		3	2.0	5.9	24.1		4	2.8	8.2	24.1		R	1.3	3.8	11.3		<p>540/1000 RPM &amp; Ground Drive 279mm PTO Clutch Independant Control</p> <hr/> <p style="text-align: center;">FUEL TANK - 62 litre capacity</p> <hr/> <p style="text-align: center;">STEERING - Hydrostatic steering</p> <hr/> <p style="text-align: center;"><b>FRONT AXLE</b> 4WD — Heavy duty front axle, centre drive epicyclic reduction in front hub. Non spin diff lock. Fully hydrostatic steering. 2WD — Telescopic sliding axle.</p>	<p>Engine Driven Hyd Pump 41 LPM Capacity Position/Draft Control Cat II 3 Point Linkage Max Lift 2350kg Operating Pressure 2600 psi</p>	<p><b>703 DT</b> Wheelbase 2215mm Overall Length 3600mm Height 2510mm Weight 3300kg Wheel Equipment: 9.5 x 24 Front, 18.4 x 30 Rear</p> <p><b>703 2wd</b> Wheelbase 2210mm Overall Length 3600mm Height 2510mm Weight 2920kg Wheel Equipment: 750 x 18 Front, 18.4 x 30 Rear</p>
	L	M	H	Range																														
1	1.1	3.4	10.0																															
2	1.6	4.7	13.7																															
3	2.0	5.9	24.1																															
4	2.8	8.2	24.1																															
R	1.3	3.8	11.3																															

# UNIVERSAL 533

<p><b>ENGINE</b>                  4 Stroke Diesel                  Direct Injection                  3cy 2696cc Capacity                  Bore x Stroke = 102 x 110mm                  56HP Max (53 Din)                  Max Torque = 162NM @ 1400                  Rotary CAV Fuel Pump                  Oil Bath Air Cleaner with Pre Cleaner</p>	<p><b>TRANSMISSION</b>                  12F x 3R                  Fully Synchronmesh                  279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>L</th> <th>M</th> <th>H</th> <th>Range</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.7</td> <td>2.1</td> <td>7.8</td> <td></td> </tr> <tr> <td>2</td> <td>1.0</td> <td>3.2</td> <td>11.7</td> <td></td> </tr> <tr> <td>3</td> <td>1.5</td> <td>4.7</td> <td>17.1</td> <td></td> </tr> <tr> <td>4</td> <td>2.0</td> <td>6.1</td> <td>22.2</td> <td></td> </tr> <tr> <td>R</td> <td>1.0</td> <td>3.1</td> <td>11.2</td> <td></td> </tr> </tbody> </table> <p>Heavy Duty Rear Axle                  BRAKES - Oil immersed wet discs                  DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	0.7	2.1	7.8		2	1.0	3.2	11.7		3	1.5	4.7	17.1		4	2.0	6.1	22.2		R	1.0	3.1	11.2		<p><b>PTO</b>                  540/1000 RPM &amp; Ground Drive                  279mm PTO Clutch                  Independant Control</p> <hr/> <p>FUEL TANK - 62 litre capacity</p> <hr/> <p>STEERING - Hydrostatic steering</p> <hr/> <p><b>FRONT AXLE</b>                  4WD — Heavy duty front axle, centre drive                  epicyclic reduction in front hub. Non spin diff lock.                  Fully hydrostatic steering.                  2WD — Telescopic sliding axle</p>	<p><b>HYDRAULIC SYSTEM</b>                  Engine Driven Hyd Pump                  34 LPM Capacity                  Position/Draft Control                  Cat II 3 Point Linkage                  Max Lift 2150kg                  Two DIA Remotes Std                  Operating Pressure 2600 psi</p>	<p><b>DIMENSIONS</b>                  533 DT                  Wheelbase 2130mm                  Overall Length 3640mm                  Height 2450mm                  Weight 2660kg                  Wheel Equipment:                  9.5 x 20 Front, 14.9 x 28 Rear</p> <p>533 2wd                  Wheelbase 2125mm                  Overall Length 3490mm                  Height 2450mm                  Weight 2470kg                  Wheel Equipment:                  650 x 16 Front, 14.9 x 28 Rear</p>
	L	M	H	Range																														
1	0.7	2.1	7.8																															
2	1.0	3.2	11.7																															
3	1.5	4.7	17.1																															
4	2.0	6.1	22.2																															
R	1.0	3.1	11.2																															

# UNIVERSAL 643

<p>4 Stroke Diesel                  Direct Injection                  4cy 3595cc Capacity                  Bore x Stroke = 102 x 110mm                  68HP Max (64 Din)                  Max Torque = 206NM @ 1400                  Rotary CAV Fuel Pump                  Oil Bath Air Cleaner with Pre Cleaner</p>	<p>12F x 3R                  Fully Synchronmesh                  279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>L</th> <th>M</th> <th>H</th> <th>Range</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.9</td> <td>2.9</td> <td>10.6</td> <td></td> </tr> <tr> <td>2</td> <td>1.4</td> <td>4.4</td> <td>16.0</td> <td></td> </tr> <tr> <td>3</td> <td>2.1</td> <td>6.5</td> <td>23.5</td> <td></td> </tr> <tr> <td>4</td> <td>2.7</td> <td>8.4</td> <td>30.3</td> <td></td> </tr> <tr> <td>R</td> <td>1.3</td> <td>4.2</td> <td>15.3</td> <td></td> </tr> </tbody> </table> <p>Heavy Duty Rear Axle                  BRAKES - Oil immersed wet discs                  DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	0.9	2.9	10.6		2	1.4	4.4	16.0		3	2.1	6.5	23.5		4	2.7	8.4	30.3		R	1.3	4.2	15.3		<p>540/1000 RPM &amp; Ground Drive                  279mm PTO Clutch                  Independant Control</p> <hr/> <p>FUEL TANK - 62 litre capacity</p> <hr/> <p>STEERING - Hydrostatic steering</p> <hr/> <p><b>FRONT AXLE</b>                  4WD — Heavy duty front axle, centre drive                  epicyclic reduction in front hub. Non spin diff lock.                  Fully hydrostatic steering.                  2WD — Telescopic sliding axle.</p>	<p>Engine Driven Hyd Pump                  34 LPM Capacity                  Position/Draft Control                  Cat II 3 Point Linkage                  Max Lift 2150kg                  Two DIA Remotes Std                  Operating Pressure 2600 psi</p>	<p><b>643 DT</b>                  Wheelbase 2270mm                  Overall Length 3780mm                  Height 2450mm                  Weight 2750kg                  Wheel Equipment:                  9.5 x 24 Front, 16.9 x 30 Rear</p> <p>643 2wd                  Wheelbase 2265mm                  Overall Length 3690mm                  Height 2420mm                  Weight 2740kg                  Wheel Equipment:                  750 x 18 Front, 16.9 x 30 Rear</p>
	L	M	H	Range																														
1	0.9	2.9	10.6																															
2	1.4	4.4	16.0																															
3	2.1	6.5	23.5																															
4	2.7	8.4	30.3																															
R	1.3	4.2	15.3																															

# UNIVERSAL 703

<p>4 Stroke Diesel                  Direct Injection                  4cy 3759cc Capacity                  Bore x Stroke = 102 x 115mm                  75HP Max (70 Din)                  Max Torque = 235NM @ 1400                  Rotary CAV Fuel Pump                  Oil Bath Air Cleaner with Pre Cleaner</p>	<p>12F x 3R                  Fully Synchronmesh                  279mm Heavy Duty Clutch</p> <p>Speeds kph @ 2400 RPM</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>L</th> <th>M</th> <th>H</th> <th>Range</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1.1</td> <td>3.4</td> <td>10.0</td> <td></td> </tr> <tr> <td>2</td> <td>1.6</td> <td>4.7</td> <td>13.7</td> <td></td> </tr> <tr> <td>3</td> <td>2.0</td> <td>5.9</td> <td>24.1</td> <td></td> </tr> <tr> <td>4</td> <td>2.8</td> <td>8.2</td> <td>24.1</td> <td></td> </tr> <tr> <td>R</td> <td>1.3</td> <td>3.8</td> <td>11.3</td> <td></td> </tr> </tbody> </table> <p>Heavy Duty Rear Axle                  Planetary Reductions                  BRAKES — Oil immersed wet discs                  DIFF LOCK - Mechanical on Rear/Auto</p>		L	M	H	Range	1	1.1	3.4	10.0		2	1.6	4.7	13.7		3	2.0	5.9	24.1		4	2.8	8.2	24.1		R	1.3	3.8	11.3		<p>540/1000 RPM &amp; Ground Drive                  279mm PTO Clutch                  Independant Control</p> <hr/> <p>FUEL TANK - 62 litre capacity</p> <hr/> <p>STEERING - Hydrostatic steering</p> <hr/> <p><b>FRONT AXLE</b>                  4WD — Heavy duty front axle, centre drive                  epicyclic reduction in front hub. Non spin diff lock.                  Fully hydrostatic steering.                  2WD — Telescopic sliding axle.</p>	<p>Engine Driven Hyd Pump                  41 LPM Capacity                  Position/Draft Control                  Cat II 3 Point Linkage                  Max Lift 2350kg                  Operating Pressure 2600 psi</p>	<p><b>703 DT</b>                  Wheelbase 2215mm                  Overall Length 3600mm                  Height 2510mm                  Weight 3300kg                  Wheel Equipment:                  9.5 x 24 Front, 18.4 x 30 Rear</p> <p>703 2wd                  Wheelbase 2210mm                  Overall Length 3600mm                  Height 2510mm                  Weight 2920kg                  Wheel Equipment:                  750 x 18 Front, 18.4 x 30 Rear</p>
	L	M	H	Range																														
1	1.1	3.4	10.0																															
2	1.6	4.7	13.7																															
3	2.0	5.9	24.1																															
4	2.8	8.2	24.1																															
R	1.3	3.8	11.3																															