

bühler

B56

tool carrier

articulating four wheel drive wheel loader



Meet the specialist in just about everything

Here is the North American built Buhler 56 articulating wheel loader that gives you the most In multi task flexibility.


Designed and produced by Buhler Manufacturing with almost 70 years of achievement in design and production of a wide range of proven, dependable equipment, you can count on engineering excellence and long term parts supply.



Left: The cab of the Buhler 56 tilts for servicing.




Below: The 56 is shown with a matching snow blower attachment.



There is a variety of tools available specifically for the B56 but if that isn't enough, this universal adapter will expand your choices to any skid steer tool available.

Attachments

The Buhler 56 supports a variety of attachments from pallet forks to snow blowers.



B56 Technical Data

Breakout force (theoretical)	4176.8 kg	9200 lbs
Tipping load straight (bucket pin)	3450.4 kg	7600 lbs
Tipping load full turn (bucket pin)	2724 kg	6000 lbs
Operating wgt/less bucket	4316.6 kg	9508 lbs
A. 1. Overall length incl. Bucket	5000 mm	196.85"
2. Overall length without bucket	4295 mm	169.09"
B Centre of axle to bucket pin	1020 mm	40.15"
C Wheel base	1950 mm	76.8"
D Rear overhang	1325 mm	52.16"
E Overhead loading height	3180 mm	125.2"
F Bucket pivot point	3420 mm	134.6"
G Height to seat	1295 mm	51"
H Max dump clearance	2801 mm	110.3"
I Max digging	51 mm	2"
J Oscillating rear axle		10 degrees
K Max reach	378 mm	14.9"
L Max height to top of cab	2388 mm	94"
M Max working height	4095 mm	161.2"
N Max dump angle		45 degrees
O Roll back angle		48 degrees
P Roll back at max. Height		48 degrees
R Total width (standard tires)	1710 mm	67.3"
T Ground clearance	258 mm	10.16"
V Width of cab	1295 mm	51"
W Wheel gauge	1395 mm	54.9"
Q Inner turning radius	1005 mm	39.5"
S Outer turning radius	2770 mm	109"
U Turn angle		55 degrees
Z Max. turning circle radius	3327 mm	131"
Engine HP/type	Kubota 56 BHP 4 cyl. Turbo	
Max torque	at 2200 RPM	
Driving speed	0-24 kph	0-15 mph
Equipment hydraulic pressure flow	200 bar/64.5 l/min	3000 psi/17 gpm
Drive line hydraulic pressure flow	400 bar/78.5 l/min	6000 psi/21 gpm

Big advantages for operator and owner:

Advanced ergonomics provide the ultimate in handling convenience, comfort and visibility. Superior operating efficiency starts with unmatched fuel economy in relation to task performance. It's built for lifecycle value with longer tire wear and rugged construction of every component. The B56 is built for the long run; a joy to operate and a pleasure to own.

For more information...

talk to your dealer or contact Buhler Manufacturing 1201 Regent Ave. West Winnipeg, Manitoba R2C 3G2 Ph. 204-661-8711

Fax: 204-654-2503

E-mail: info@buhler.com

Website: www.buhler.com

Equipment shown here may be changed at any time without notice or obligation.

