

QUALITY

ENGINEERED TO PERFORM BETTER
FOR LONGER

Giltrap

GRASS TOPPERS



WHEN YOU NEED MACHINERY TO WORK BETTER AND LAST LONGER YOU
KNOW YOU CAN RELY ON GILTRAP



**PRECISION
GRASS**

Giltrap's reputation for durability is perhaps best illustrated by the performance of their new Grass Topper range.

Spreading over five models from 1.2 metres (true cutting width) to 3.0 metres (true cutting width) the Giltrap Topper is built for long-term reliability.

Like most modern toppers the Giltrap range features simple, easy-to-clean body lines, but some features set them apart from other manufacturers.

■ M3000 TWIN ROTOR HIGH SPEED TOPPER

- 3.0m (9' 10") true cutting width
- Heavy gearbox drive systems : centre 64HP, outer 80HP, 1:2.16 total ratio
- Gearboxes protected by shock absorption drive couplings
- Twin rotors each with two reversible spring steel flails, mounted on an anti-scalping disc
- Cutting height set with easily adjustable skids
- Hard-wearing, replaceable skid shoes
- 3 point linkage mounted
- Heavy duty construction
- Topper body has a hinged centre spine and adjustable trailing wheel. With tractor hydraulic arms set to position control, this wide topper follows ground contours as well as smaller machines
- Over-running clutch standard on PTO shaft
- Ideal for cutting pasture, light scrub or stubble
- Recommended horsepower: 60-80HP without limiting clutch



M3000 Twin Rotor High Speed Topper



Trailing Land Wheel

■ M2300 TWIN ROTOR HIGH SPEED TOPPER

- 2.3m (7'6") true cutting width
- Heavy gearbox drives: centre 64HP, outer 80HP, 1:2.90 total ratio
- Gearboxes protected by shock absorption drive couplings
- Twin rotors each with two reversible spring steel flails, mounted on an anti-scalping disc
- Cutting height set with easily adjustable skids
- Hard-wearing, replaceable skid shoes
- 3 point linkage mounted
- Strong construction
- 'Lead-in' and 'trailing' centre skids to follow ground contours
- Ideal for parks and reserves, golf courses, light scrub and pasture
- Recommended horsepower: 45-65HP without limiting clutch



M2300 Twin Rotor High Speed Topper

■ OPTIONAL E

- PTO limiting clutches
- Alternative flails - N
- S

giltrap

ENGINEERED TOPPERS

- All models are gearbox driven.
- All models feature extra strong chassis construction.
- All feature reversible high tensile spring steel cutting blades.
- All feature easily replaceable hard wearing shoe plates fitted on to skids.
- All models are designed to accurately follow variations in ground contour.
- Model M3000 and M2300 feature additional central skids.
- Model M3000 features an easily adjustable land wheel.



■ M1500 4 BLADE TOPPER

- 1.50m (5') true cutting width
- Low horsepower requirement
- 64HP gearbox 1:1.47 ratio
- Single rotor with 4 swinging flails, secured by high tensile pins to a round cutting disc
- Cutting height set with easily adjustable skids
- Hard-wearing, replaceable skid shoes
- 3 point linkage mounted
- Robust construction
- Ideal for light scrub and pasture
- Recommended horsepower: 35-65HP without limiting clutch



M1500 4 Blade Topper



M1500 2 Blade High Speed Topper

■ M1500 2 BLADE HIGH SPEED TOPPER

- 1.50m (5') true cutting width
- 64HP gearbox 1:1.97 ratio
- Single rotor with 2 swinging flails, attached to an anti scalping disc
- Cutting height set with easily adjustable skids
- Hard-wearing, replaceable skid shoes
- 3 point linkage mounted
- Robust construction
- Ideal for light scrub and pasture
- Recommended horsepower: 35-65HP without limiting clutch



■ M1200 3 BLADE HIGH SPEED TOPPER

- 1.20m (47.5") true cutting width
- 40HP gearbox 1:1.97 ratio
- Single rotor with 3 swinging flails
- Cutting height set with easily adjustable skids
- Hard-wearing, replaceable skid shoes
- 3 point linkage mounted, easily set off-centre to either side
- Light but durable construction
- Ideal for horticulture and small farms
- Recommended horsepower: 20-40HP



M1200 3 Blade High Speed Topper

EXTRAS

Normal sharpened downwards
Special mower type blades for quick regrowth

Giltrap

PRECISION ENGINEERED GRASS TOPPERS M3000 M2300 M1500 (4 BLADE OR HI SPEED) M1200

S P E C I F I C A T I O N S

	M1200	M1500	M2300	M3000
Number of rotors	1	1	2	2
Number of blades	3	2 or 4	4	4
Gearbox (Corner)	One 40 H.P. Right Angle Box	One 64 H.P. Right Angle Box	One 64 H.P.'T' and Two 80 H.P. Right Angle Boxes	One 64 H.P.'T' and Two 80 H.P. Right Angle Boxes
Anti-Scalping Discs	-	On high speed rotor only	Yes	Yes
Adjustable skids	Yes	Yes	Yes	Yes
Body type	Rigid	Rigid	Rigid	Hinged
Cutting Width	1.2m (47.5")	1.5m (5')	2.3m (7'6")	3.0m (9'10")
Replaceable Hard Wearing Skid Shoes	Yes	Yes	Yes	Yes
Measurements				
Height	.98m	1.05m	.95m	.95m
Width	1.42m	1.68m	2.50m	3.25m
Length	1.40m	1.75m	1.75m	2.25m
Weight	190kg	270kg	470kg	610kg
Floating Top Link	Yes	Yes	Yes	Yes
Outer G/Box Protection	N/A	N/A	Shock Absorption Drives	Shock Absorption Drives
Recommended Horsepower	20-40H.P.	35-65H.P.	45-65H.P.	60-80H.P.



Heavy Duty Gearboxes



M2300 Shock Absorption Coupling



Heavy Duty Driveshafts



M3000 Shock Absorption Coupling



Special mower type cutting blades for quick regrowth

Your local Giltrap Agent is:



The Manufacturer reserves the right to change specifications or prices without prior notice.

For further information on these or any other Giltrap products, please contact:



ENGINEERING LTD

3 Main North Rd., P.O. Box 83, Otorohanga, New Zealand. Ph: 07 873 7199, Fax: 07 873 8131